

TYRE BUFFERS, RIVETER & SPRAY GUN

For professionals who settle for nothing less than excellence, AIRCAT's Tyre Buffers, Riveters, and Spray Guns are the go-to tools. These high-performance tools are engineered to optimize productivity and minimize downtime, delivering exceptional results across a variety of industries. Whether you're working on heavy-duty tyres, precise riveting, or smooth finishing with spray guns, AIRCAT tools are built to tackle demanding tasks with ease.



WHEN YOU HAVE REAL WORK TO DO...
GRAB AN AIRCAT.



6400 COMPOSITE HIGH SPEED TYRE BUFFER / DRILL								
SPEED (RPM)	MOTOR (HP)	SPINDLE THREAD SIZE (IN.)	CHUCK SIZE (IN.)	WEIGHT (KG)	LENGTH (MM)	AIR CONS. (CFM)	REC. HOSE SIZE (IN.)	AIR INLET (IN.)
22,000	0.75	3/8 x 24"	3/8"	0.75	203	4	3/8"	1/4"

- ERGONOMIC MOLDED HANDLE
- LOW NOISE
- HIGH CONTROL



TUNE-UP KIT CONTAINS SPARES NO.:
2, 3, 10, 17, 18, 20, 26



6402 0.60 HP 2,600 RPM COMPOSITE TYRE BUFFER								
SPEED (RPM)	MOTOR (HP)	SPINDLE THREAD SIZE (IN.)	CHUCK SIZE (IN.)	WEIGHT (KG)	LENGTH (MM)	AIR CONS. (CFM)	REC. HOSE SIZE (IN.)	AIR INLET (IN.)
2,600	0.60	3/8 x 24"	5/16" INTERNAL HEX	0.79	228	3.5	3/8"	1/4"

- **AC6403:** 0.60 HP | 3,600 RPM | COMPOSITE TYRE BUFFER
- ERGONOMIC MOLDED HANDLE
- LOW NOISE
- COMFORTABLE



TUNE-UP KIT CONTAINS SPARES NO.:
2, 3, 8, 11, 16, 19, 24, 29, 31



NEW

6410 3/16" AIR HYDRAULIC RIVETER				6420 1/4" AIR HYDRAULIC RIVETER			
RIVET SIZES	REC. HOSE SIZE (IN.)	AIR INLET (IN.)	PULLING FORCE (KG)	RIVET SIZES	REC. HOSE SIZE (IN.)	AIR INLET (IN.)	PULLING FORCE (KG)
3/8"	3/8"	1/4"	907	3/8"	3/8"	1/4"	1,678

- RIVET SIZES:
 - 5/32 INCH ≈ 3.97 MM
 - 3/16 INCH ≈ 4.76 MM
- PROFESSIONAL-GRADE DESIGN SUITABLE FOR CONTINUOUS OPERATION

- RIVET SIZES:
 - 3/16 INCH ≈ 4.76 MM
 - 1/4 INCH ≈ 6.35 MM
 - 3/16 INCH MONOBOLT ≈ 4.76 MM
- MONOBOLT
 - 1/4 INCH MONOBOLT ≈ 6.35 MM



TUNE-UP KIT CONTAINS SPARES NO.:
2, 3, 8, 11, 16, 19, 24, 29, 31



NEW

6900 HVLP GRAVITY FEED SPRAY GUN - 1.4 MM					
WEIGHT (KG)	AIR CONS. (CFM)	OPERATING RANGE	STANDARD AIRCAP SET (MM)	AIR SUPPLY HOSE WIDTH	AIR INLET (IN.)
0.54	12.5	14-28 PSI	1.4	5/16"	1/4"

- SMOOTH/COMFORTABLE TRIGGER PULL
- INCLUDES GEN 1 QUICK TWIST-LOCK SPRAY GUN CUP ADAPTER
- HVLP SPRAY GUN FOR FINE FINISH PAINT ON CARS, INDUSTRY, AND WOODWORK



TUNE-UP KIT CONTAINS SPARES NO.:
3,4,6,15,16,20,29,42,44



NEW

6905 HVLP GRAVITY FEED SPRAY GUN - 1.7 MM					
WEIGHT (KG)	AIR CONS. (CFM)	OPERATING RANGE	STANDARD AIRCAP SET (MM)	AIR SUPPLY HOSE WIDTH	AIR INLET (IN.)
0.54	12.5	14-28 PSI	1.7	5/16"	1/4"

- HVLP TECHNOLOGY REDUCES PAINT WASTE AND AIR VOLUME
- STAINLESS STEEL NEEDLES FOR ULTIMATE RELIABILITY
- PRECISION BRASS SPRAY CAPS FOR PERFECT PATTERN



TUNE-UP KIT CONTAINS SPARES NO.:
3,4,6,15,16,20,29,42,44

