



4450

Composite Drill - Keyed Chuck

FEATURE

- 1/2" reversible composite drill.
- Keyed chuck.
- Feather trigger for better speed control.
- Trigger mounted reverse for instant change of direction.
- Superior grade steel planetary gear for longer life.
- 400 rpm.
- Patented quiet tuned exhaust (85 dba).
- Patented ergonomically designed handle.
- Air flow pressure: 90 psi.

SPECIFICATIONS

Free speed (rpm): 400
Motor (hp): 0.70
Chuck Size (in.): 1/2
Gears: Planetary

Weight (kg): 1.36
Length (mm): 203.25
Vibration level M/ Sec2: 1.0
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



4451

COMPOSITE DRILL - Chuck & Key or
Keyless Chuck Option

FEATURE

- 0.70 hp motor.
- Low weight composite housing reduces weight.
- Patented one-click reverse button provides instant change of direction.
- Patented "silencing technology" reduces the noise level to 83 dba.
- Patented grip has been ergonomically designed to perfectly fit the hand providing unmatched comfort for the user.
- Forward position handle allows operator to apply increased feed force.
- Forward position handle allows more control for drilling pilot hole and more control to maintain the drilled hole axis.

SPECIFICATIONS

Free speed (rpm): 400
Motor (hp): 0.70
Chuck Size (in.): 1/2
Gears: Caged Planetary

Weight (kg): 1.86
Length (mm): 235.45
Vibration level M/ Sec2: 2.5
Air Consistency (CFM): 9
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



4337

Angle Drill - Chuck & Key

FEATURE

- 0.75 hp motor.
- Precision spiral bevel gears increase reliability.
- Conveniently positioned forward/reverse knob.
- Built-in speed regulator for added control.
- Ergonomically designed composite over-mold grip and throttle lever provide unmatched comfort for the user.
- Fitted with grease nipple for gear lubrication.
- Internal silencing reduces noise level to 75 dba.
- Rear exhaust directs air away from work area.
- Fitted with keyed chuck.

SPECIFICATIONS

Free speed (rpm): 1,600

Motor (hp): 0.75

Chuck Size (in.): 3/8

Gears: Spiral Bevel

Spindle Thread Size (in.): 3/8 x 24

Weight (kg): 1.08

Length (mm): 210.82

Vibration level M/ Sec2: 2.1

Air Consistency (CFM): 6

Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURE

- 3/8" reversible composite drill.
- Jacobs® chuck (keyless).
- Feather trigger for better speed control.
- Trigger mounted reverse for instant change of direction.
- 1,800 rpm.
- Superior grade steel planetary gear for longer life.
- Patented quiet tuned exhaust (85 dba).
- Patented ergonomically designed handle.
- Air flow pressure: 90 psi.

SPECIFICATIONS

Free speed (rpm): 1,800
Motor (hp): 0.70
Chuck Size (in): 3/8
Gears: Planetary
Spindle Thread Size (in.): 3/8 x 24

Weight (kg): 1.13
Length (mm): 177.80
Vibration level M/ Sec2: 1.7
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM