



3128XPA - Mini Random Orbital Sander

- Engineered for the most aggressive sanding applications
- Delivers swirl-free finishes when feather edging, removing rust, preparing metal surfaces, or smoothing welds
- Durable ball-bearing construction ensures smooth power delivery
- Includes 3" (75 mm) hook and loop style backing pads

3128KA - Mini Random Orbital Sander Kit

- Includes 3128XPA
- Includes 71-piece hook and loop discs and pad :
 - 180, 220, 320 and 800 grits aluminum oxide
 - backing pad



3129XPA - Mini Polisher

- Ideal for buffing and polishing paint, metal, and plastic surfaces to a high-gloss finish
- Free speed of 6,400 rpm delivers the same performance of polishers twice the size
- Double-sided, adjustable speed settings provide variability for a broader range of applications
- Includes 3" (75 mm) hook and loop style backing pads

3129KA - Mini Polisher Kit

- Includes 3129XPA
- Includes four-piece hook and loop pads with foams



	CCN	Pad Size in/mm	Free Speed rpm	Rated Power KW	Net Weight kg	Overall Length mm	Air Consumption l/min	Vibration level/ uncertainty (K) m/s ²	Sound Level ² dB(A)
Air Sander									
3128XPA	47520749001	3" (75 mm)	15,000	0.15	0.6	145	513	5.2 - 1.1 m/s ²	80,9
3128KA	47520770001	3" (75 mm)	15,000	0.15	1.5	145	513	5.2 - 1.1 m/s ²	80,9
Air Polisher									
3129XPA	47520771001	3" (75 mm)	6,400	0.22	0.6	155	561	2.7 - 0.7 m/s ²	81,5
3129KA	47520750001	3" (75 mm)	6,400	0.22	1.5	155	561	2.7 - 0.7 m/s ²	81,5

(1) ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

(2) ISO15744) Performance at 90 PSI (6,2 bar) Air inlet NPTF 1/4" (6mm). Min hose size 3/8" (10mm).



3103XPA - Mini Surface Prep Sander

- Ideal for the removal of rust, surface deposit and welds in hard-to-reach areas
- Ball-bearing construction enhances durability and smooth power delivery
- Double-sided, adjustable speed settings provide variability for a broader range of applications
- Includes 2" (50 mm) and 3" (75 mm) medium backing pads

3103KA - Mini Surface Prep Sander Kit

- Includes 3103XPA
- Includes 14-piece 2" (50mm) and 3" (75mm) sanding discs and pads



7804XPA - 6,5 mm Mini Drill/Driver

- Hard-hitting five-vane motor delivers smooth and robust performance
- Double-sided, adjustable speed settings provide variability for a broader range of applications
- Double-bearing construction for longer life, impressive balance, and reduced vibration

7804KA - 6,5 mm Mini Drill/Driver Kit

- Includes 7804XPA
- Includes 22-piece drill bit and driver set



	CCN	Pad Size in/mm	Free Speed rpm	Rated Power KW	Net Weight kg	Overall Length mm	Air Consumption l/min	Vibration level ⁽¹⁾ / uncertainty (K) m/s ²	Sound Level dB(A)
Air Sander									
3103XPA	47520748001	2" & 3" (50 & 75 mm)	15,000	0.15	0.5	135	538	4.1 - 0.8 m/s ²	78,6
3103KA	47520769001	2" & 3" (50 & 75 mm)	15,000	0.15	1.6	135	538	4.1 - 0.8 m/s ²	78,6
	CCN	Chuck capacity mm/in	Free Speed rpm	Rated Power KW	Weight kg	Overall Length mm	Air Consumption l/min	Vibration level ⁽¹⁾ / uncertainty (K) m/s ²	Sound Level dB(A)
Air Drill/Driver									
7804XPA	47520751001	6,5 mm (1/4")	1.875	0.19	0.8	193	459	2.9 - 0.8 m/s ²	84,3
7804KA	47520772001	6,5 mm (1/4")	1.875	0.19	1.85	193	459	2.9 - 0.8 m/s ²	84,3

(1) ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

(2) ISO15744) Performance at 90 PSI (6,2 bar) Air inlet NPTF 1/4" (6mm). Min hose size 3/8" (10mm).