PROTRONIC® ELECTRONIC TORQUE WRENCHES





The ProTronic[®] is a high precision electronic torque wrench with a large backlit LCD display, that measures accurate and consistent torque readings. It also features an audible buzzer when pre-set torque/angle value is reached.

- Dual progressive LEDs positioned both sides of the wrench provide an easy visual representation of torque progress allowing the user to more easily anticipate torque target
- Large LCD screen with bright backlight; numbers become larger and bolder during active torque for optimal viewing
- Four alert modes (LCD, progressive LED, audible, vibration) provide excellent feedback in all working conditions
- 5 easily selectable torque units: N·m, lbf·ft, lbf·in, dN·m, kg·cm and kg·m (200 N·m and above)

ROMOTE

- The ability to programme up to 10 pre-sets in the tool saves time in setting up frequently occurring applications
- A wide range of advanced features (cycle counter, customisable sleep timer, language selection, auto torque calculation for torque adaptors, calibration alerts, battery level indication, and numerous alert mode customisations) allow the user to tailor the tool to their work preferences
- Torque THEN Angle mode gives the user the ability to conveniently apply an angle to a fastener directly after achieving a torque target without the need to remove the torque wrench from the application
- Settings allow for operation in either English, Spanish, French, German, Italian, Dutch or Portuguese
- Power interruption technology helps to prevent loss of work and continuity if the wrench is impacted
- Patent pending built-in calibration factor feature allows different head lengths to be easily accommodated
- Handle designed for a comfortable and secure grip
- Battery cap has been designed to prevent accidental loosening
- Storage case included
- Supplied with a traceable 'Calibration Certificate' conforming with ISO 6789-2:2017, allowing end users to adhere to more stringent quality control processes

4	PROTRONIC
130517	ProTronic 100, ¾", 5 - 100 N·m
130518	ProTronic 100, ½", 5 - 100 N·m
130519	ProTronic 200, ½", 10 - 200 N⋅m
130520	ProTronic 340, ½", 17 - 340 N·m






Dual progressive LEDs positioned both sides of the wrench provide an easy visual representation of torque progress


PROTRONIC® ELECTRONIC TORQUE WRENCHES



Model		ProTronic 100 ¾"	ProTronic 100 ½"	ProTronic 200 ½"	ProTronic 340 ½"
Part Number		130517	130518	130519	130520
	А	458	462	650	749
	В	439	439	627	723
Dimensions	С	344	344	533	629
(mm)	ØD	38	46	46	52
	E	34	45	45	45
	F	21	29	29	29
Weight (kg)		1.15	1.30	1.65	1.85











- Accuracy of $\pm 2\%$ when operating between 20% to 100% of tool capacity.

• Angle accuracy of ±1% of reading, ±1° @ Angular Velocity >10°/Sec < 180°/Sec, ±1° for test fixture