

# FASTENING



*Pistol grip for horizontal applications or for better controllability*



*In-line shape for vertical applications*

## HOW TO SELECT YOUR FASTENING SCREWDRIVERS?

### STEP 1

#### Applications

- ▶ Materials/Fasteners
- ▶ Joint types
- ▶ Accuracy
- ▶ Torque/Speed
- ▶ Duty

### STEP 2

#### Screws

- ▶ Shape
- ▶ Size
- ▶ Access
- ▶ Bits

### STEP 3

#### Tools

- ▶ Clutch type
- ▶ Torque/Speed
- ▶ Handle type

### CLUTCH TYPE

#### ▶ IMPACT CLUTCH (ROCKING DOG)

- Good on very soft joints providing high speed rundown

#### ▶ DIRECT DRIVE

- No clutch, directly driven bit
- Stall torque regulated to air pressure
- Easy to use by maintain
- Ergonomic handling (light weight, size...)

#### ▶ POSITIVE CLUTCH

- Good for varying torque applications
- Operator can force clutch engagement for higher torque
- Excellent for wood applications

#### ▶ CUSHION CLUTCH

- High speed rundown
- Torque output adjusted by spring tension
- Clutch ratchets at preset torque
- Easy to use, adjust and to maintain

#### ▶ SHUT-OFF CLUTCH

- Clutch shut-off at preset torque
- Various speed models available
- Torque adjustment for accurate tightening
- Various shapes for all types of applications



#### CLUTCH TYPES

#### IMPACT

#### DIRECT

#### POSITIVE

#### CUSHION

#### SHUT-OFF



SUPER INDUSTRIAL

CP2754  
CP2764

CP2816 - CP2817  
CP2826 - CP2829

CP2003 - CP2005  
CP2007 - CP2008  
CP2010 - CP2012



INDUSTRIAL MAINTENANCE AND PRODUCTION

CP2755  
CP2765

CP2780

CP2623 - CP2612  
CP780 - CP781  
CP781

CP2611  
CP2621  
CP2622



GENERAL MAINTENANCE

CP2036 - CP2037  
CP2041 - CP2042  
CP2136 - CP2141

[illegible]

## Impact Clutch Screwdrivers

**CP2136** ★

10,000 RPM

COMPACT, FAST  
& EASY TO USE**FEATURES**

- 1/4" Hex quick change
- Double rocking dog clutch
- Single hard reverse

**BENEFITS**

- Compact & Lightweight
- Low air consumption for a better efficiency
- Excellent for various MRO applications



CP2141

**CP2141** ★

13,000 RPM

COMPACT, FAST &amp; EASY TO USE

**FEATURES**

- 1/4" Hex bits
- Double rocking dog clutch
- Single hard reverse

**BENEFITS**

- Compact & Lightweight
- Low noise level for operator comfort
- Excellent for various MRO applications

**CP2141**

See accessories on pages 65-66

★ GENERAL MAINTENANCE
★★ INDUSTRIAL MAINTENANCE & PRODUCTION
★★★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	K	ISO 15744 - dB(A)		in.
CP2136	894 102 1360	1/4	10,000	5.93	8.0	15.5	21.0	1.5	0.7	7.3	185	8.8	4.2	7.4	2.8	89	100	1/4
CP2141	894 102 1410	1/4	13,000	7.38	10.0	17.7	24.0	1.9	0.9	5.6	143	18.1	8.5	5.3	2.1	77	88	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

# FASTENING

## Impact Clutch Screwdrivers

### CP2041 ★

15,000 RPM



#### FAST & FURIOUS

##### FEATURES

- Double rocking dog clutch
- Reversible
- Suspension bail included

##### BENEFITS

- High Torque and High Speed
- Comfortable handling with Ergo-grip
- Operator comfort with single handed

### CP2042 ★

5,600 RPM



#### COMPACT & HIGH TORQUE

##### FEATURES

- Double rocking dog clutch
- Reversible
- Suspension bail included

##### BENEFITS

- High power delivered with controlled speed
- Comfortable handling with Ergo-grip
- Operator comfort

### CP2036 ★

10,000 RPM



### CP2037

Same features as CP2036 with higher torque

#### LOW NOISE & LIGHTWEIGHT

##### FEATURES

- Double rocking dog clutch
- Built-in power regulator
- Ergonomic with suspension bail

##### BENEFITS

- Low noise & lightweight
- Quick torque adjustment
- Excellent for soft type materials



CP2041



See accessories on pages 65-66

★ GENERAL MAINTENANCE ★ INDUSTRIAL MAINTENANCE & PRODUCTION ★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2036	615 192 2036	1/4	10,000	2.5	3.4	11.8	16.0	1.7	0.8	8.2	207	13.0	6.1	<2.5	-	83	94	1/4
CP2037	615 192 2037	1/4	10,000	13.3	18.0	20.7	28.0	1.8	0.8	8.2	207	13.0	6.1	<2.5	-	88	99	1/4
CP2041	615 192 2041	1/4	15,000	5.9	8.0	31	42.0	2.3	1.0	5.9	152	27.0	12.7	3.1	1.3	88	99	1/4
CP2042	615 192 2042	1/4	5,600	4.4	6.0	30.2	41.0	2.3	1.0	5.9	152	27.0	12.7	6.6	3.3	88	99	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.



## Positive Clutch &amp; Direct Drive Screwdrivers

**CP2780** ★★

2,100 RPM

COMPACT & HIGH SPEED  
POSITIVE CLUTCH

## FEATURES

- Reverse control at the trigger
- Progressive trigger
- Rubber grip

## BENEFITS

- Perfectly designed for wood applications
- Operator can control clutch engagement for higher torque
- Good for prevailing torque applications

**CP2755** ★★

2,200 RPM

HIGH-SPEED DIRECT  
DRIVE

## FEATURES

- Reverse control at the trigger
- Rubber grip
- Progressive trigger

## BENEFITS

- Good for soft draw applications
- Fast screw rundown
- Compact & easy handling

**CP2765**Similar features as  
CP2755 with higher torque

IDEAL FOR USE WITH  
STUD CLEANERS (PG. 61)  
TO IMPROVE THE  
CLAMPING FORCE OF  
TIGHTENING



CP2755

**CP2764** ★★★

600 RPM

DURABLE & LOW  
NOISE FOR INTENSIVE  
APPLICATIONS

## FEATURES

- Reliable motor & components
- Durable Aluminum Body
- Progressive trigger

## BENEFITS

- Robust construction & Simple maintenance
- Comfortable handling and noise level only (77dB(A))
- Powerful & continuous screw penetration

**CP2754**Same features as  
CP2764 with higher speed

See accessories on pages 65-66

★ GENERAL MAINTENANCE   ★★ INDUSTRIAL MAINTENANCE & PRODUCTION   ★★★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2754	615 192 2754	1/4	1,450	3.7	5.0	2.0	0.9	8.3	210	17.0	8.0	<2.5	-	77	88	1/4
CP2755	615 192 2755	1/4	2,200	5.4	7.3	2.3	1.0	6.3	160	29.7	14.0	<2.5	-	90	101	1/4
CP2764	615 192 2764	1/4	600	10.3	14.0	2.2	1.0	9.0	228	17.0	8.0	<2.5	-	77	88	1/4
CP2765	615 192 2765	1/4	900	6.6	9.0	2.6	1.2	7.0	178	29.7	14.0	<2.5	-	99	110	1/4
CP2780	615 192 2780	1/4	2,100	7.4	10.0	2.4	1.1	6.5	164	29.7	14.0	<2.5	-	89	100	1/4

Hose int. 3/8"(10mm) @90 PSI (@6.3 Bar) (CP2754 and CP2764)  
Hose int. 1/2"(13mm) @90 PSI (@6.3 Bar) (CP2755, CP2765, CP2780)

Listed specifications are for reference only. Please check documents in each tool.

# FASTENING

## Cushion Clutch Screwdrivers

**CP780** ★★



1,800 RPM



### HIGH SPEED & ROBUST

#### FEATURES

- External clutch adjustment
- Built-in 1/4" Female Hex quick-change
- Convenient single handed forward/reverse

#### BENEFITS

- High speed fastening for greater productivity
- Reliable & easy-to-adjust cushion clutch
- Ideal tool for general repair, wood, PVC & refurbishing applications

**CP782** ★★



1,800 RPM



### CP783

Same features as CP782 with higher speed and lightweight

### HIGH TORQUE & ROBUST

#### FEATURES

- External clutch adjustment
- Convenient single handed forward/reverse valve
- Progressive lever start and suspension bail

#### BENEFITS

- Reliable cushion clutch
- Comfortable use thanks to low weight
- Ideal tool for general assembly operations on metal, wood, PVC, or any repair applications

**CP781** ★★



800 RPM



### HIGH TORQUE & ROBUST

#### FEATURES

- External clutch adjustment
- Built-in 1/4" Female Hex quick-change
- Convenient single handed forward/reverse

#### BENEFITS

- Reliable & easy-to-adjust cushion clutch for powerful fastening
- Robust aluminum body & steel clutch housing
- Ideal tool for general assembly, metal, wood, PVC and refurbishing applications



CP781



See accessories on pages 65-66

★ GENERAL MAINTENANCE   ★★ INDUSTRIAL MAINTENANCE & PRODUCTION   ★★★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP780	T025095	1/4	1,800	2.06	2.8	3.7	5.0	2.5	1.1	8.3	210	25.0	11.6	2.9	1.4	98	109	1/4
CP781	T025096	1/4	800	4.57	6.2	8.4	11.3	3.0	1.4	8.9	226	25.0	11.8	<2.5	-	100	111	1/4
CP782	T025097	1/4	1,800	2.58	3.5	3.7	5.0	2.5	1.1	9.6	245	16.1	7.6	<2.5	-	94	105	1/4
CP783	T025098	1/4	2,000	0.8	1.1	2.06	2.8	1.3	0.6	8.9	226	9.0	4.2	<2.5	-	88	99	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

## Cushion Clutch Screwdrivers

**CP2623** ★★

1,800 RPM

EXTREMELY COMPACT  
& PRODUCTIVE**FEATURES**

- Single handed reverse button
- Keyless Torque setting adjustment
- Color rings for torque identification

**BENEFITS**

- Productive at 1,800 rpm
- Compact for easy access
- Low noise & vibration for operator comfort

**CP2612** ★★★

1,700 RPM

VERY COMPACT,  
COMFORTABLE & VERSATILE**FEATURES**

- 3 air inlets for greater versatility
- Keyless Torque setting adjustment
- Color rings for torque identification

**BENEFITS**

- Fast at 1,700 rpm
- Compact for easy access
- Low noise & vibration for operator comfort

**CP2612**SPEED IS KEY TO IMPROVE  
PRODUCTIVITY WITH CUSHION  
CLUTCH MODELS

See accessories on pages 65-66

★ GENERAL MAINTENANCE    ★★ INDUSTRIAL MAINTENANCE &amp; PRODUCTION    ★★★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2612	615 192 2612	1/4	1,700	0.737	1.0	4.42	6.0	2.0	0.9	7.5	190	21.2	10.0	<2.5	-	77	88	1/4
CP2623	615 192 2623	1/4	1,800	1.106	1.5	4.056	5.5	1.8	0.8	8.2	207	27.8	13.1	<2.5	-	78	89	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

# FASTENING

## Cushion Clutch screwdrivers

**CP2816** ★★ ★

1,900 RPM



FOR INTENSIVE USE

### FEATURES

- Robust aluminium housing
- Comfortable rubber grip
- Convenient single handed fwd/rev operation

### BENEFITS

- Durable mechanism
- Quick torque setting
- Good for many applications

**CP2817** ★★ ★

800 RPM



FOR MRO AND ASSEMBLY

### FEATURES

- Up to 6.3 ft.lbs (8.5 Nm)
- Comfortable rubber grip
- Convenient single handed fwd/rev operation

### BENEFITS

- Robust aluminium housing
- Comfortable rubber grip

**CP2828** ★★ ★

1,600 RPM



**CP2829**

Similar features as CP2828 with higher torque

INDUSTRIAL & SLIM

### FEATURES

- Small diameter - good grip
- High speed
- Low noise and vibration level

### BENEFITS

- Robust aluminium housing
- Comfortable rubber grip
- Convenient single handed fwd/rev operation



CP2828



See accessories on pages 65-66

★ GENERAL MAINTENANCE ★ INDUSTRIAL MAINTENANCE & PRODUCTION ★★ ★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2816	615 163 0020	1/4	1,900	1.8	2.5	3.4	4.6	2.6	1.2	8.3	210	28.2	13.3	5.2	1.2	84	95	1/4
CP2817	615 163 0030	1/4	800	2.2	3.0	7	9.5	2.9	1.3	9.0	230	28.4	13.4	6.6	1.2	84	95	1/4
CP2828	615 163 0040	1/4	1,600	1.3	1.8	2.4	3.2	1.3	0.6	7.7	195	15.0	7.1	0.3	0.8	73	84	1/4
CP2829	615 163 0050	1/4	750	1.8	2.5	3.8	5.2	1.3	0.6	7.7	195	15.0	7.1	0.3	0.8	73	84	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.



## Shut-Off Clutch Screwdrivers

**CP2621** ★★

1,000 RPM



EASY HIGH TORQUE  
SETTING FOR VARIOUS  
ACCURATE TYPES OF  
ASSEMBLY

**FEATURES**

- Straight Push-to-start operation
- Keyless Torque setting adjustment
- Color rings for torque identification

**BENEFITS**

- Versatile thanks to wide & high torque range
- Low Noise for operator comfort
- Excellent accuracy for various applications

**CP2622** ★★

1,700 RPM



PRODUCTIVE,  
ACCURATE &  
COMFORTABLE

**FEATURES**

- Convenient single handed fwd/rev operation
- Keyless Torque setting adjustment
- Color rings for torque identification

**BENEFITS**

- Productivity thanks to high speed
- Easy to operate thanks to ergonomics features
- Excellent accuracy for versatile applications

**CP2611** ★★

1,000 RPM

PRODUCTIVE & ACCURATE  
PISTOL SHUT-OFF

**FEATURES**

- 3 air inlets for greater versatility
- Keyless Torque setting adjustment
- Color rings for torque identification

**BENEFITS**

- Versatile thanks to wide & high torque range
- Limited Noise level for operator comfort
- Excellent accuracy & easy torque adjustment

**CP2611**

WITH 3 AIR INLETS, THIS CP2611 CAN  
BE USED IN VERTICAL AND HORIZONTAL  
APPLICATIONS



See accessories on pages 65-66

★ GENERAL MAINTENANCE   ★★ INDUSTRIAL MAINTENANCE & PRODUCTION   ★★★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2611	615 192 2611	1/4	1,000	0.737	1.0	5.53	7.5	2.4	1.1	9.3	235	21.2	10.0	<2.5	-	80	91	1/4
CP2621	615 192 2621	1/4	1,000	0.59	0.8	4.79	6.5	1.8	0.8	9.1	232	30.9	14.6	<2.5	-	76	87	1/4
CP2622	615 192 2622	1/4	1,700	0.368	0.5	3.32	4.5	1.8	0.8	9.1	232	29.0	13.7	<2.5	-	75	86	1/4

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.

# FASTENING

## Shut-Off Clutch Screwdrivers

**CP2005** ★★☆☆

1,100 RPM



THE MOST ROBUST  
& DURABLE PISTOL

### FEATURES

- Robust aluminum body
- Progressive trigger
- Convenient single handed fwd/rev operation

### BENEFITS

- Accurate & reliable clutch
- Ergonomic handling for Operator comfort
- Durable housing, even for heavy duty applications

**CP2008** ★★☆☆

1,100 RPM



ACCURATE & DURABLE

### CP2010

Same features as  
CP2008 with higher  
torque and higher  
speed

### FEATURES

- Accurate & durable Shut-off clutch screwdriver
- Robust Aluminum housing

### CP2012

Same features as  
CP2010 with lever start

### BENEFITS

- Ideal for multiple applications
- Perfect for disassembly

**CP2003** ★★☆☆

1,100 RPM



### CP2007

Same features  
as CP2003 with  
higher torque

COMPACT & LIGHTWEIGHT  
FOR LIGHT ASSEMBLY  
APPLICATIONS

### FEATURES

- Straight Push-to-start operation
- Convenient single handed fwd/rev operation
- Low noise level

### BENEFITS

- Compact & comfortable for production operations
- Reliable & Accurate for various fastenings



CP2003



See accessories on pages 65-66

★ GENERAL MAINTENANCE   ★ INDUSTRIAL MAINTENANCE & PRODUCTION   ★ SUPER INDUSTRIAL

MODEL	PART NUMBER	OUTPUT HEX	FREE SPEED	MIN TORQUE		MAX TORQUE		NET WEIGHT		LENGTH		FREE SPEED AIR CONS.		VIBRATION LEVEL ISO 28927 (m/s <sup>2</sup> )		SOUND PRESS.	SOUND POWER	AIR INLET
		in.	rpm	ft.lb	Nm	ft.lb	Nm	lb	kg	in.	mm	cfm	l/s	a	k	ISO 15744 - dB(A)		in.
CP2003	615 192 2003	1/4	1,100	0.295	0.4	1.106	1.5	0.9	0.4	7.7	197	8.5	4.0	<2.5	-	73	84	1/8 BSP
CP2005	615 192 2005	1/4	1,100	0.295	0.4	3.17	4.3	1.8	0.8	7.2	182	13.8	6.5	<2.5	-	76	87	1/8 BSP
CP2007	615 192 2007	1/4	1,100	0.295	0.4	3.17	4.3	1.3	0.6	9.8	250	13.8	6.5	<2.5	-	81	92	1/8 BSP
CP2008	615 192 2008	1/4	1,100	0.295	0.4	3.17	4.3	1.5	0.7	10.8	275	13.8	6.5	<2.5	-	76	87	1/8 BSP
CP2010	615 192 2010	1/4	1,470	1.475	2.0	4.056	5.5	2.0	0.9	10.0	253	19.1	9.0	<2.5	-	76	87	1/8 BSP
CP2012	615 192 2012	1/4	1,470	1.475	2.0	4.056	5.5	2.0	0.9	10.9	278	19.1	9.0	<2.5	-	73	84	1/4 BSP

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.